

# LEGACY®

SHINGLE LINE

# FLEXOR™ POLYMER MODIFIED ARCHITECTURAL SHINGLES

Distributed from:

OR

CA

OK

77

**Shown in:**  
**Natural Wood**

[illegible]



# LEGACY® & LEGACY®



## FLEXOR™ POLYMER MODIFIED ASPHALT

Asphalt technology increases flexibility, granule adhesion, and impact resistance.



## PROTECT FROM EXTREME WEATHER

Class 4 impact resistance offers your roof the highest rated protection available.



## SCOTCHGARD™ PROTECTOR: HELP PREVENT BLACK STREAKS

Helps maintain the aesthetic appearance of your roof. Includes a 20-year warranty.



## RETAIN COLOR GRANULES

Superior granule adhesion provides your roof lasting beauty and protection from damaging solar rays.



## FORMULATED ROOFING SEALANTS

Specially formulated asphalt sealants hold the shingle in place during high winds and rain sealants protect from wind driven rain.



## SUPERIOR SHINGLE STRENGTH

Shingles with Flexor™ polymer modified asphalt are more resistant to tearing and nail pull-out, reducing the risk of shingle blow-off.



## THE ZONE®: IMPROVE FASTENER PLACEMENT

The Zone® nailing area dramatically improves correct fastener placement during installation.




## FLEXIBLE IN ALL WEATHER

Asphalt technology provides flexibility for application in a wider range of climates and roof styles.




## \*\* WIND WARRANTIES

110 mph (177 kph) Limited Wind Warranty included. Eligible for a 130 mph (209 kph) Enhanced Wind Warranty when conditions are met.



ANTIQUE BROWN



BLACK OAK



HEATHER



MIDNIGHT BLACK



NATURAL WOOD




OXFORD GREY



RAINFOREST



SIENNA BLEND



SILVERWOOD



STORM GREY



WEATHERED WOOD



## FEATURING

- Limited Lifetime Shingle Warranty
- 15-year Right Start™ Warranty

## TEST COMPLIANCE

- ASTM D7158 Class H
- ASTM D3462
- ASTM D3018 Type I
- UL 2218 Class 4
- ICC Approval – ESR-3150
- ASTM D3161 Class F
- ASTM E108 Class A Fire Rating
- CSA A123.5
- FBC Approval – #14809



GREENCIRCLE CERTIFIED  
MANUFACTURING FACILITY

DISCLAIMER: Sample pieces or photographs of shingles may not accurately represent the true color or variations of color blends that will appear on the roof. Before installation, five or six shingles should be laid out and reviewed for conformity to desired color level. If color levels are unsatisfactory, advise your dealer before proceeding with installation. Colors and specifications subject to change without notice. Shingle colors not available in all regions. Limited warranties carry terms and conditions. Please contact your local Malarkey representative for color availability and further information. See Malarkey's Shingle and Accessory Warranty for details.

\* For complete Limited Lifetime Warranty details, reference Malarkey's Shingle and Accessory Warranty.

\* Malarkey shingles featuring Scotchgard™ Protector must be installed with EZ-Ridge™ (8", 10") or RidgeFlex™ (10", 12") hip and ridge products, which feature Scotchgard™ Protector, to receive Malarkey's full 20-year Algae Resistant Shingle warranty. The Alaskan® featuring Scotchgard™ Protector can be substituted as hip and ridge shingles, in conjunction with Malarkey shingles featuring Scotchgard™ Protector, to receive the full Malarkey 20-year Algae Resistant Shingle warranty. Scotchgard and the Scotchgard logo, including the 3M logo, are all trademarks of 3M.

\*\* Shingles come with a 110 mph (177 kph) Limited Wind Warranty. Eligible for a 130 mph (209 kph) Enhanced Wind Warranty when Smart Start™ starter shingles are installed, shingles are 6-nailed, and either EZ-Ridge™ (8", 10") or RidgeFlex™ (10", 12") hip and ridge shingles are used. Some contractors adapt roofing shingles to use as hip and ridge shingles. Use of The Alaskan® as a hip and ridge shingle will apply towards the Enhanced Wind Warranty. Dura-Seal™ shingles used for hip and ridge will not qualify toward an Enhanced Wind Warranty. Malarkey performance-driven underlayments – Arctic Seal®, Right Start™ UDL, or SecureStart™ – are recommended for added system protection. This version supersedes all previous versions. Rev. 7/16



**Malarkey**  
Roofing Products®  
Defining Excellence.™

P.O. BOX 17217, PORTLAND, OR 97217  
503.283.1191 | 800.545.1191 | FAX: 503.289.7644

**WWW.MALARKEYROOFING.COM**